

TECHNICAL SPECIFICATIONS

► Chassis:

- Volvo FL H18, 4 x 2 (Vestergaard spec.) EURO 6 engine
- Automatic gearbox 6-Speed Alison306

► Colour scheme:

- Chassis cabin and tank section: White colour (RAL 9016 equal to Volvo 1107)
- Boom system: Light Grey (RAL 7040)

► Tank:

- 5600 liter pre-mix type I, 2000 liter type II/IV
- Stainless steel tanks with 5 year warranty
- Tank 2 is thermal insulated from tank 1
- Pipes for bottom filling As standard capped with 2" threads

► Heating System

- 230 kW diesel total heating capacity Three separate heaters in parallel setup
- Batch heating system, as ensure a quick start-up time.
- Automatic fire extinguish system Novac 1230

► Fluid systems

- One circulation pump Type-I compatible max. flow rate 210±10 l/min.
- One pump diaphragm Type-I/II/IV compatible max. flow rate 120±10 l/min
- Separate tubing of Type I and Type II/V fluid to basket To reduce spillage by change in sprayed fluid type

► Performance - lift system:

- Fully proportional operation of boom system.
- Open basket design
- Working LED-light at basket
- Max. rated load in basket: 205 kg
- Boom construction sandblasted and quality coated corrosion class C4-high

► Information display in truck cabin

- Tank level indication
- Temperature in tank 1 and batch tank



For questions and requests for further information please contact:

Vestergaard Company A/S

Skulbjerg 31 • Gevninge
DK-4000 Roskilde • Denmark
Tel: +45 4642 2222
Fax: +45 4642 2232
sales@vestergaardcompany.com
www.vestergaardcompany.com

Vestergaard Company Inc.

1721 N. Oak Drive
McHenry, IL 60050 • USA
Tel: +1 815 759-9102
Fax +1 815 759-9103
Toll free: +1 888 759-9118
usa@vestergaardcompany.com

Vestergaard Company SASU

17 L route de Creil
95340 Bernes sur Oise
Tel.: +33 1 30 34 55 87
france@vestergaardcompany.com

Caution: Specifications are advisory only, and will vary. Please request exact data.

OPTIONS

► Options:

- Ground gun in left side behind truck cabin. Max hose length 15 meter Only able to spray tank 1 fluid
- Access into tanks via manhole covers and steps/ladder left side
- Spare wheel front/rear
- Basket Side Cover To protect the operator in the basket from the weather
- Amber flashing beacon Located at hydraulic tank
- Side guard on chassis – left or/and right side In order to prevent underride collisions
- Coupling for bottom filling Stortz, Camlok, Guillemain, Todo, Elaflax
- Hot at nozzle for pre-mix system To insure instant heated fluid at spray gun in basket
- Additional spray gun in basket

