

FILLING UNIT

DE-ICING SYSTEMS

Vestergaard Company's mobile filling unit is kept simple in its design making it both easy and safe to use. Maintenance requirements are also kept to a minimum with the use of stainless steel.

By using gentle diaphragm pumps the unit is applicable for all kinds of de-icing fluids. It is a reliable, small unit fit for many years of intense use.

Furthermore the unit has a very high mobility with its compact design and big, stable rubber wheels.



Standard unit:

- Max capacity 270 litre/min.
- Various pump speed
- Temperature up to 90 degree Celsius
- Compact design, easy stowage, fits onto standard euro-palletise for easy storage and transport.
- 3x400 Volt 50 HZ max 8 Amp
- 16 Amp CEE plug with 10 meter rubber cable
- 2 x 5 metre 2" hoses standard mounted with 2" Kamlok aluminium couplings
- Unit weight 250 kg.

Options:

- Other voltage/HZ possibly.
- Various types of fluid couplings.
- Automatic shutdown of pump, "Requires top-level sensor on de-icing truck".

MAJOR ADVANTAGES

- » Easy to use
- » High safety
- » Low maintenance
- » High mobility
- » Fits onto standard euro-palletise
- » Applicable for all kinds of de-icing fluids.

Vestergaard Company A/S
Skullebjerg 31 • Gevninge
DK-4000 Roskilde • Denmark
Tel: +45 4642 2222
Fax: +45 4642 2232
sales@vestergaardcompany.com
www.vestergaardcompany.com

Vestergaard Company Inc.
1721 N. Oak Drive
McHenry, IL 60050 • USA
Tel: +1 815 759-9102
Fax: +1 815 759-9103
Toll free: +1 888 759-9118
usa@vestergaardcompany.com

COMPANY
VESTERGAARD