

## TECHNICAL SPECIFICATIONS

- **Chassis:**
  - Europe: Volvo FL250, 4 x 2 (Vestergaard spec.) EURO 6 engine, Allison automatic transmission
  - North America: International 4x2 Model MV607 (Vestergaard spec.), Allison automatic transmission
- **Colour scheme:**
  - Chassis cabin and tank section: White colour (RAL 9016 equal to Volvo 1107 )
  - Boom system: Light Grey (RAL 7040)
- **Tank:**
  - 5600 liter pre-mix type I, 2000 liter type II/IV
  - Stainless steel tanks with 5 year warranty
  - Tank 2 is thermal insulated from tank 1
  - Pipes for bottom filling. As standard capped with 2" threads
- **Heating System**
  - 230 kW diesel total heating capacity. Three separate heaters in parallel setup
  - Batch heating system, as ensure a quick start-up time.
  - Automatic fire extinguish system. Novec 1230
- **Fluid systems**
  - One circulation pump Type-I compatible max. flow rate 210±10 l/min.
  - One pump diaphragm Type-I/II/IV compatible max. flow rate 120±10 l/min
  - Separate tubing of Type I and Type II/V fluid to basket to eliminate spillage when changing sprayed fluid type
  - Onboard filling function for both tanks
- **Performance - lift system:**
  - Fully proportional operation of boom system.
  - Open basket design
  - Working LED-light at basket
  - Max. rated load in basket: 205 kg
  - Boom construction sandblasted and quality coated corrosion class C4-high
- **Information display in truck cabin**
  - Tank level indication
  - Temperature in tank 1 and batch tank



Heating system for ADF with three in-line heaters



Simple operation panel in basket



Volvo FL 250



International MV607

For questions and requests for further information please contact:

**Vestergaard Company A/S**  
 Skullevjerg 31 • Gevinge  
 DK-4000 Roskilde • Denmark  
 Tel: +45 4642 2222  
 sales@vestergaardcompany.com  
 www.vestergaardcompany.com

**Vestergaard Company Inc.**  
 1903 W. Rte. 120  
 McHenry, IL 60051 • USA  
 Tel: +1 815 759-9102  
 Toll free: +1 888 759-9118  
 usa@vestergaardcompany.com

**Vestergaard Company SASU**  
 Bâtiment 3450 A, 4, Rue du Té  
 93290 Tremblay-en-France • France  
 Tel.: +33 1 30 34 55 87  
 france@vestergaardcompany.com

**Vestergaard Company Ltd.**  
 Pinthong Industrial Estate  
 789/50 Moo 1, Nongkham  
 Chonburi 20230 • Thailand  
 Tel: +66 (0) 38 348 630  
 asia@vestergaardcompany.com

Caution: Specifications are advisory only, and will vary. Please request exact data.

## OPTIONS

### ► Options:

- Ground gun in left side behind truck cabin. Max hose length 15 meter Only able to spray tank 1 fluid
- Access into tanks via manhole covers and steps/ladder left side
- Spare wheel front/rear
- Basket Side Cover. To protect the operator in the basket from the weather
- Amber flashing beacon. Located at hydraulic tank
- Side guard on chassis – left or/and right side In order to prevent underride collisions
- Coupling for bottom filling. Stortz, Camlok, Guillemmin, Todo, Elaflex
- Hot at nozzle for pre-mix system. To insure instant heated fluid at spray gun in basket
- Additional spray gun in basket
- One-man operation from basket
- Reverse camera
- Level display at side of tank section
- Flow sensor for sprayed fluid
- Basket sensor for safety

